



Capacities

* Refill capacity is approx. 0.7 litre (1.125 imp. pt) less than the from dry figures.

The following capacities are only an approximation of the amount of fluid required to fill the respective system.

Capacities – UK/ROW

| Component / system | Capacity |
|--|------------------------------|
| Fuel tank: | |
| ⇒ Td4 Model | 59 litres (13 gallons) |
| ⇒ K1.8 & KV6 Model | 65 litres (14.3 gallons) |
| Engine - Td4 (including oil cooler and oil filter): | |
| ⇒ Refill | 6.8 litres (12 imp. pts) |
| ⇒ Fill from dry | 7.3 litres (12.9 imp. pts) |
| Engine - K1.8 (including filter): | |
| ⇒ Refill | 4.5 litres (7.9 imp. pts) |
| ⇒ Fill from dry | 4.8 litres (8.4 imp. pts) |
| Engine - KV6 (including oil cooler and filter): | |
| ⇒ Refill | 5.2 litres (9.125 imp. pts) |
| ⇒ Fill from dry | 6.0 litres (10.625 imp. pts) |
| Manual gearbox - PG1: | |
| ⇒ Refill | 2.0 litres (3.5 imp. pts) |
| ⇒ From dry | 2.2 litres (3.9 imp. pts) |
| Manual gearbox - Getrag: | |
| ⇒ Refill | 1.6 litres (2.875 imp. pts) |
| ⇒ From dry | 1.67 litres (3 imp. pts) |
| Automatic gearbox - JATCO: | |
| ⇒ Refill | 4.0 litres (7 imp. pts) |
| ⇒ From dry† | 8.5 litres (15 imp. pts) |
| Intermediate Reduction Drive | 1.1 litres (2 imp. pts) |
| Rear differential: | |
| ⇒ Maximum | 830 ml (29.2 imp. fl. oz.) |
| ⇒ Minimum | 750 ml (26.4 imp. fl. oz.) |
| Power steering reservoir | 335 cm ³ |
| Cooling system - Td4 Engine – Fill from dry (with reservoir)*: | |
| ⇒ Automatic | 7.25 litres (12.8 imp. pts) |
| ⇒ Manual | 7.25 litres (12.8 imp. pts) |
| Cooling system - K1.8 Engine: | |
| ⇒ Fill from dry (with reservoir)* | 5.8 litres (10.25 imp. pts) |
| Cooling system - KV6 Engine: | |
| ⇒ Fill from dry (with reservoir)* | 7.8 litres (13.75 imp. pts) |
| Reservoir tank: | |
| ⇒ Maximum fill | 0.44 litres (0.75 imp. pts) |
| ⇒ Expansion tank volume | 1.2 litres (2.125 imp. pts) |
| ⇒ Gross expansion capacity | 0.72 litres (1.27 imp. pts) |
| Windscreen washer reservoir | 4.0 litres (7 imp. pints) |

† An extra 420 cc (0.73 imp pt) is required for vehicles with an air blast fluid cooler fitted.